

DIGITAL INDUSTRIES SOFTWARE

Opcenter Execution Discrete

Optimizing production processes and driving operational excellence while improving time-to-market

Executive summary

Customers are increasingly able to directly tell manufacturers what they want and when they want it. As a result, manufacturers must respond quickly with improved flexibility to enable individualized mass production while reducing energy and resource consumption. Merely focusing on the automation of manufacturing processes or on the cost and efficiency of individual production operations is no longer enough to compete in the global marketplace. It is necessary to take an approach that spans the entire value chain and includes suppliers.

Siemens Digital Industries software now offers a holistic automation solution covering all major Industry 4.0 requirements. Manufacturers are better equipped to initiate or respond to disruptive innovation trends when their processes are fully digitalized.

SIEMENS

Contents

Introduction	3
Why focus on manufacturing operations management?	4
How you can succeed	6
Opcenter Execution Discrete	8
Collaborations	32
Integration with automation, physical	
devices and third-party system	34
Conclusion	36

Introduction

1.1 A holistic approach to optimize the entire value chain

Siemens solutions connect major parts of the product and production lifecycle. Powerful product lifecycle management (PLM) software enables the development and optimization of new products on an entirely virtual basis.

To digitally transform the realization phase, Siemens provides a complete portfolio of solutions for manufacturing operations management (MOM), bridging PLM and automation domains and enabling customers to implement strategies for the complete digitalization and integration of their product and production lifecycles.

The Siemens portfolio for manufacturing operations management enables the digitalization of a broad spectrum of production-related functions, including advanced planning and scheduling, manufacturing execution, quality management and manufacturing intelligence. These solutions are used in tandem to optimize production processes and drive operational excellence with a focus on steadily improving production efficiency, flexibility, and time-to-market. **Improved efficiency.** The Siemens MOM portfolio provides end-to-end visibility into production operations and quality management, connecting the automated operations equipment and systems on the shop floor to the decision-makers in product development, manufacturing engineering, production and enterprise management. With full visibility into production, decision-makers can readily identify areas to be improved within both the product design and associated manufacturing processes and make the necessary operational adjustments for smoother and more efficient production.

Improved flexibility and time-to-market.

Using the Siemens MOM portfolio, our customers can model, visualize, optimize, update and harmonize production processes globally, and can collect, plan and schedule, aggregate, analyze and respond to real-time manufacturing events. The integration with PLM, enterprise resource planning (ERP) and automation provides the flexibility and scalability of production processes required to maximize responsiveness. With a fully optimized digital enterprise, manufacturers are better equipped to rapidly respond to market changes and realize the innovation that customers demand today.

2 Why focus on manufacturing operations management?

On a daily basis, a variety of people in charge of different activities face problems that involve manufacturing systems. Implementing MOM and deploying the right production model can provide a solution to many of these issues. In broad outline, the problems encountered concern:

- Business
- Production
- Information technology (IT)

2.1 Business issues

Increase the overall efficiency of your supply chain

Supply-chain efficiency is strongly affected by how the business level (ERP) and the shop floor (control) interact. MOM represents the go-between that, when streamlined and efficient, contributes to a better supply chain.

React quickly to new conditions and market requirements

In manufacturing, the ability to adapt to new operational requirements (for example, changes in product specifications or quality procedures) and environmental conditions (for example, introduction of new standards) is paramount to success. If your system is ready to meet these challenges, the reward may be a significant increase in your competitiveness as well as significant cost savings.

Standardize production process across all plants

Guaranteeing uniform, consistent production procedures is a key issue. If this is lacking, then the result may be uneven quality of your product from one facility to another. Control systems and business systems cannot solve the problem; a structured and modeled environment is required to coordinate the production process seamlessly and in different contexts (for example, different hardware and software installation bases).

Comply with new regulations

Established standards and regulations such as International Organization for Standardization (ISO) or the German Association of the Automotive Industry (VDA) already exist to guarantee highquality products. However, new regulations, as well as the need for exhaustive material traceability, are substantially affecting manufacturing procedures. MOM can be used to help you achieve compliance with these regulations and maintain a complete accounting of materials.

Make your business more customer-oriented

Standard monolithic applications often represent a barrier to implement an efficient system that can adapt and satisfy ever-changing requirements from both the customer and the market. In view of the growing demands posed by customers, MOM can make your system much more flexible and adaptable. With a fully optimized digital enterprise, manufacturers are better equipped to rapidly respond to market changes and realize the innovation that customers demand.

2.2 Production issues

Rework, scrap and materials management

Typically, rework and scrap cannot be handled by control systems. Without appropriate management, excessive waste or uncontrolled material tracking can also affect the quality of your final product. In addition, overall material tracking throughout the production process is now a crucial factor for both accounting and the correct evaluation of production costs.

Increase visibility with production-related KPIs and advanced reporting

To comprehend fully how your plant is performing, you need a system that can generate production reporting correlating process control-specific data with production-related data (order number, lots, personnel, materials, etc.) to facilitate troubleshooting and analyze performance problems. MOM can increase visibility into the production process, creating the right conditions to promote improvement and increase your manufacturing system's efficiency.

Improve quality, pinpoint defects

Without tools to accurately identify defective lots and back track production, you may be unable to address specific issues regarding the quality of your product. You may also be unable to respond to customer complaints appropriately or organize product recalls promptly. An efficient MOM system can provide complete genealogy to track materials throughout the entire production process. It also follows all material transformations with precision until the final product is produced and delivered to the end customer.

React efficiently to production problems, reduce downtime

What if something goes wrong on the shop floor? Efficient management of failures and downtimes is needed. Often, several systems need to be involved in solving the problem (maintenance must be informed, rescheduling is required, personnel must be notified as soon as possible). Poor coordination leads to using resources ineffectively, ultimately raising your production costs.

2.3 IT issues

Integrate and synchronize systems, reduce maintenance costs

A myriad of links between your software solutions greatly increases the complexity of the manufacturing system. In turn, costs for IT maintenance and program modification become staggering. This is mainly due to the lack of coordination and flexibility of most manufacturing applications. The modeling approach can effectively simplify integration and actively coordinate the interaction and the flow of information between different applications on site.

Reduce implementation costs and risks

Employing reusable solutions creates the conditions for streamlining and accelerating project implementations. Total ownership costs can be cut dramatically thanks to efficiently reusing software.

Share and re-use know-how and expertise

Efficient re-use of software is key to realizing cost savings. Being able to "code" the expertise enables the rapid transfer of know-how between users, which is usually not feasible with standard applications. Without a modeling environment to help you define business procedures that focuses on the production process rather than specific IT issues, it is difficult to understand complex manufacturing applications, making it virtually impossible to modify or re-use code.

Maintain your team's technological skills, reduce training costs

Applications are very often numerous and customized to satisfy specific needs. As a result, the person with the most thorough know-how is frequently asked to develop and maintain these applications. Such competence is difficult and expensive to maintain. By adopting a solution that covers all functionalities in an integrated and homogenous environment, complex manufacturing systems can be implemented with ease, making the tasks involved workable even for those users with mainstream skills.

3 How you can succeed



MOM architectural model.

3.1 Opcenter Execution Discrete

Manufacturing environments are becoming more exacting, and manufacturers need solutions from their suppliers that provide tangible benefits with quantifiable and quick return-on-investment (ROI). To increase competitiveness, manufacturers must reduce time-to-market and cope with shorter product lifecycles, increase visibility and comply with regulatory demands, optimize forecasting and scheduling and reduce scrap, stock levels and downtimes: all while ensuring optimal quality and production efficiency across global facilities. In an enterprise IT architecture, this means enabling communication and integration between the key teams that are contributing to bringing products to market.

To rationalize and speed up processes, product design/ideation data needs to be transferred seamlessly to the engineering environment, where the manufacturing process and test/inspection points are defined. The engineering process is the critical link between product ideation and manufacturing. It is where ideas become industrialized reality. It can be done more rapidly when this data is transferred seamlessly to the manufacturing floor for execution. Interoperability with the financial/administration software can enhance real-time capabilities and supply chain efficiency, enabling the user to manage customer orders and transfer them to the manufacturing level.

In parallel, the production floor also needs to be equipped and organized to produce efficiently, avoiding unforeseen problems with equipment capacity, energy use, etc. Therefore, the digital factory/plant lifecycle management part of the Siemens portfolio enables virtual testing and commissioning of plants and their equipment, delivering upfront required configurations for the automation layer, which in turn communicates with the manufacturing execution level.

Opcenter[™] software and Teamcenter[®] software are part of the Siemens Xcelerator business platform of software, hardware and services. Their combination enables integration of the product and production lifecycle, resulting in faster time-to-market. Opcenter Execution Foundation is a manufacturing execution system (MES) that supports manufacturers by enhancing productivity and flexibility with leading-edge technology combined with industry-specific features.

Opcenter Execution Discrete is specialized for addressing the needs of the discrete industry market, focusing on job-shop part manufacturing and complex manual assembly. The Siemens closed-loop manufacturing (CLM) solution provides a way to bring together product engineering and process planning with production execution and automation: both engineering and runtime data is exchanged circularly (that is, in a closed loop), accelerating the adoption of any changes or corrective measures necessary for improving quality and lead time.

The Siemens CLM solution is based on the integration between Teamcenter Manufacturing software and Opcenter Execution Discrete.

3.2 Business benefits

Using Opcenter Execution Foundation fills the gap between business level systems (typically PLM, ERP, supply chain management, etc.) and control systems, providing the conditions for increasing overall supply chain efficiency. Opcenter Execution Foundation provides manufacturing systems with native flexibility that enables users to easily adapt and modify the business process for new requirements and business drivers.

- Using Opcenter Execution Foundation enables manufacturers to model their businesses to be much more customer-oriented and ready to satisfy any on-the-fly requirements from the market
- Using Opcenter Execution Foundation supports a flexible scalability concept by design, allowing customers to scale and distribute their system as required in a cost-effective way
- As vertical product Opcenter Execution Discrete comes off the shelf with industry-specific features to cover discrete manufacturing processes
- Opcenter Execution Discrete allows users to comply with existing regulations

3.3 Production benefits

Opcenter Execution Discrete offers a set of modules able to cover the MOM core requirements in the context of job-shop part manufacturing and complex manual assembly. By modeling and defining production procedures, Opcenter Execution Discrete effectively increases visibility into the entire production process:

- Close alignment and synchronization between product design and production environments
- The ability to introduce product design changes while production has already started
- Operator guidance to ensure timely and correct execution
- Traceability, genealogy and visibility of work-in process (WIP), which are essential to understand current production status and support decision-making
- Deviations and nonconformances can be managed most effectively, tying into customizable sentencing and rework processes

 Support for mobility as a wide range of devices may be used as clients

3.4 IT benefits

The Opcenter Execution Foundation product family combines the benefits of a platform for developing and orchestrating custom use cases with predefined industry-specific, off-the-shelf functionality, as is the case with Opcenter Execution Discrete:

- Standard industry-specific functionality immediately available
- Ability to modify existing features and develop new functionality
- Built-in scalability allows tailoring investment and maintenance according to case-by-case requirements
- Ability to connect and interact with external and legacy IT systems

4 Opcenter Execution Discrete

4.1 General overview

To manage high tech special devices, the user needs to manage production complexity, improve quality, reduce costs and shorten time-to-market. Opcenter Execution Discrete (Opcenter EX DS) is used to implement a tailored MES for complex job-shop organized factories and provides the following functions:

- Production process and flow control
- MOM integrated with product lifecycle management
- Production route enforcement

- Execution management
- Tracking and tracing
- Defect tracking and nonconformance management
- · Paperless manufacturing and reporting
- Electronic data collection
- · Additive manufacturing support

Opcenter EX DS is a software product that was specifically designed and developed by Siemens by leveraging the Opcenter Execution Foundation technology.

Production process and flow control

- Allocate operator activity to production operations, steps, material items and resources
- Accurate WIP management of orders, operations, batches and serial numbers
- Distribute workload among operators at shift start, taking their skills into account; ability to define teams of operators working on the same operations

e	Process AMN_MJF_PA12_NoD	yeing_Process	y ra the set of the se	و SIEMENS
谷	t↓ D @ ≢	As Planned BOPs and Processes > Process AMN_MJF_PA12_N	↓oDyeing_Process	
3	AM_Cylinder_BOP	Details Operations Process Operation Dependencies	Sub-Processes Alternative Operations	
4	Material: DE_Cylinder	Zoom:	Auto Fit Pan and Zoom	
9 <u>8</u>	Plant: AM-Demo-Site	AMN Pret(10) AMN in-Preter Cooling(20) Amn ind	After End	Alwind
	AMDemo_Pyr_Proc AM_Pyramid_Baseline			
()	Material: DE_Pyramid Plant: AM-Demo-Site			
	AMN_MJF_PA12_Dyei			
	AMN_MJF_PA12_Dyeing_Basel			
8	Plant: AM-Demo-Site	4		•

Dependencies among process operations.

MOM integrated with PLM

- Ability to receive production processes plain or nested – ready to be executed from a PLM system (specialized features are available in the case of Teamcenter Manufacturing in the context of the CLM solution)
- Ability to create configuration-specific work orders based on variant processes
- Ability to analyze the impact of changes on planned and running work orders
- Nonconformance feedback to PLM (specialized features are available in the case of Teamcenter Manufacturing in the context of the CLM solution)
- Ability to expose plant resources from MOM to PLM to enable manufacturing engineers to address correct data

 Ability to define human resources with related skills needed to perform specific operations and ensure these constraints are followed during the production

Production route enforcement

- List operations on screen based on certified operator skills (required certificates, skills and skill level are defined at the operation level, typically in Teamcenter Manufacturing)
- Operator punch in/out on operations with time logging
- Check correctness of process steps execution
- Production scheduling using Preactor Advanced Scheduling (AS)

Execution management

- Display details of activities to be performed
- · Part assembly declaration and tracking
- Tool usage declaration
- Check for part/tool correctness
- Ability to interact with external direct numerical control (DNC) system for computer numerical control (CNC) part program transfer
- Separate labor tracking on non-productive activities



Details of activity to be performed.

Tracking and tracing

- Serial numbers of assembled materials
- Batch identifiers of transformed materials
- Measurement data collection
- Co-product tracking
- As-built report
- Genealogy report

Est. Start:	Est. Duration: 00:25:00	Remaining Time: 00:00	Status:	S Work Order	r Operation: 30-Deburring
Final Material: Machined Block	SN: MB_MAB_20201001_150	Workcenter: FabCleanStation	Active Users: S	EMENSDC\Administrator	
Q Į	Work Instructions			Document viewer	23
Work Instruction Task for Work Instruction	FabricationDeburringOp3				
Updated: Oct 1, 2020 11:22:43 AM	FabricationDeburringSection1 -	Deburring Operation			Table Division
•	FabricationDeburringStep2 - Data Collection	From Field			
Quality Inspection Task for Quality Inspection Updatest Oct 1, 2020 11:22:44 AM	Length Machined Block Length:	Data Collection		Î	
B	Low Limit: 70 High Limit: 74 Target: 72 Width		mm		1
	Machined Block Width:			5	
	Low Limit: 70 High Limit: 74 Target: 72				
	Height Machined Block Height:				
			mm		
	Low Limit: 70 High Limit: 74 Target: 72			Overation Parts Product	
			Acquire Confirm		
	COMPLETE.				

Details of data acquisition for tracking and tracing.

Defect tracking and nonconformance

- Failure tracking
- Nonconformance management based on problem catalog
- Nonconformance lifecycle management
- · Manage and execute rework processes
- Leverage the integration with Teamcenter Quality to perform planned quality inspections including visual inspections

Paperless manufacturing and reporting

- Electronic work instructions
- Data collection points
- Barcode reading support

Additive manufacturing support

- Ability to interact with CAM systems to inject serial numbers in print job files; ability to interact with 3D-printers to transfer print job files
- Track and display the genealogy of powder material batches
- Track and display the lifecycle of substrates

4.1.1 Complex manufacturing terminal

A special operator terminal has been designed for shop floor operators working in factories building complex products, such as aircraft, engines, submarines, industrial machines, etc. These kind of products are characterized by complex structures with many operations and steps and additional documents/images to be reviewed by the operator during their job.

From the complex manufacturing terminal you can perform various actions:

- Preview work order operations and work order steps
- Preview document files
- Preview work instructions
- Start work order operations
- Manage work order operations
- Manage activities for work order operation/step progression
- Manage work instructions
- Use Tools
- Consume material tracking units
- Disassemble material tracking units
- Place work orders on hold
- Pause and resume work order operations
- Quality inspections
- Create quality nonconformance
- Complete work order operations



Operator Terminal for Complex Manufacturing.

4.1.2 One Piece Flow App

This provides a screen with a simplified user interface that a company can use to show which product is present and the activities to be done, keeping in mind that few interactions are possible by users due to the fast track time.

From the Operator Terminal in One Piece Flow App, as an Operator, you can perform various actions on a specific material tracking unit (MTU):

- Make the MTU enter and exit the equipment
- Declare milestones and perform the corresponding transitions
- Execute traceability operations
- Browse failures and manage defects
- Execute generic data collection operations
- Execute screwing operations
- Declare the result of a work order operation using mandatory positive confirmations

- If the piece of equipment has been declared as quality gate, manage additional functionalities
- If a line side position is associated to the piece of equipment, manage the line side Inventory and kanban requests for the replenishment of materials

4.1.3 Multi-plant architecture support

Opcenter EX DS supports multi-plant architecture, meaning that can manage multiple factories or plants from a single central installation. This solution offers configuration both with common settings and plant-specific tuning, it's also possible to implement run-time operations with a multitenancy approach.

The main benefits of a multi-plant scenario are:

- Lower total cost of ownership due to a limited number of servers, updates and patches
- A simpler overall architecture reducing human error during system alignment
- Shorter rollout time for new plants

User: SWQA\ITA80781 Equipment: PL01.AR30.LN01.SG01.WP02U	AITEM1_87716516 ↓		
	Cool Operations SCREW OFF-ROAD WHEELS Rundown: (b. 0) (btotok-0) 10 D0-6 SCREW OFF-ROAD WHEELS Rundown: (btotok-0) 10 D0-6 SCREW OFF-ROAD WHEELS SCREW OFF-ROAD WHEELS Rundown: (btotok-0) 10 D0-6 SCREW OFF-ROAD WHEELS Rundown: (btotok-0) To D0-6 SCREW OFF-ROAD WHEELS	Details Product Id AITEM1_87716516 Code SIESISWSP00000001 Current Milestone 30X	Defects
Mandatory Positive Confirmation	Schew Orf-ROAD WREELS Rundown: Ok-0 Not Ok-0 To Do-6	Customer Type TRY-OUT Sequence	
b∕.	COLLECT THERMO PRESS DATA 1	Serial Number SIESISWSP00000001 Line Sequence PL01.AR30.LN01_0001	

Operator Terminal for One Piece Flow production.

Enabling standardization and harmonization implies less configuration effort. The new multi-plant architecture also provides great value for:

- Business continuity: a plant has no downtime during updates to other factories and during rollouts of new plants
- Security and usability: only the data related to your plant is visible and modifiable
- Robustness: the performance of one plant is not affected by workload peaks or other plant's issues

4.1.4 Industry-specific operator terminal UI

Siemens has introduced Operator Terminal, as part of Opcenter Execution Discrete. Operator Terminal is created precisely to cover specific processes and industry's needs.

These new terminals are low code user interface (UI) apps, powered by the Mendix[™] platform, which is also part of Siemens Xcelerator. Mendix platform enables our customers and partner to easily personalize the user interface to cover their specific requirements.

4.2 Opcenter Execution Discrete licenses

4.2.1 User management

User management is fundamental to any system as it permits restricting access to sensitive data while ensuring that only individuals with the appropriate know-how and position within the organization perform certain tasks.

In Opcenter Execution Discrete, the basic entities involved in user management are:

- Users and groups
- Roles
- Certifications (refer to "Certifications" chapter)

4.2.2 Users and groups

In Opcenter Execution Discrete, a user is defined as a person who can access the application. Each user has a login and a password.

The list of Opcenter Execution Discrete users is logically separate from the list of Windows users on the machine where Opcenter Execution Discrete is installed. During installation, a dedicated user (who assumes the super-user role and has administrative rights) is created from a Windows user. Additional users can be created later. A group represents a set of users who have been categorized according to specific rules. In a Windows operating system, users can be grouped. Opcenter Execution Discrete can use these Windows groups as well as create new groups.

4.2.3 Roles

Roles define which operations a user is authorized to perform; every Opcenter EX DS user has a role.

Opcenter Execution Discrete comes with predefined roles for access control. In addition, you can create custom roles to satisfy specific needs, and assign a role to a single user or to a group of users.

4.2.4 Operation work booking

A common requirement during production is to collect all the possible information regarding execution time and location of orders. This information is useful when compared with estimated time to improve order planning and engineering, but it is also useful in tracking the labor time of operators and allocating resources (both human and machine).

To satisfy this requirement, Opcenter Execution Discrete provides these capabilities:

- Track work order execution start/end time
- Track work order due time
- Track execution equipment

This set of information is tracked automatically by the system: the operator simply clicks the start button. When an operator stops working for any reason (for example, during lunch break), he/she must interrupt the execution of the operation by clicking the pause button: the system then stops tracking work time and can provide the actual execution and labor time during subsequent analysis (as-built, genealogy).

Operators can resume work at any time by again clicking the start button: the system will resume to track working time and location. Operators click the complete button when they complete operation execution: the working time counter is stopped and the operation is declared completed.

Information collected during this process is typically presented as:

- Genealogy report
- As-built report
- Custom reports

To maximize productivity and minimize equipment downtime, thereby allowing machines to work at full capacity, operations (associated with the same or different work orders) can be grouped by execution.

They are executed together at runtime on the same equipment.

4.2.5 Process management



Select and start work order operations from the operator landing page; other commands are available.

The framework for all production engineering is based on processes and how they are sequenced. A process is an abstract representation of the sequence of operations and steps involved in producing a specific product. Processes are high level outlines that illustrate how to proceed to execute a specific manufacturing activity. A process represents all operations, tools and machines to be used, and materials to be consumed to achieve a particular goal in a production activity that will be executed. Each instance of a process is referred to as a work order.

Processes can be defined directly for a specific product, or they can be generic production route templates that apply to several products; in the latter case, product-specific properties will be defined in the production orders derived from generic processes. The following elements contribute to forming a single process and are listed hierarchically:

- Subprocesses (Optional: multiple subprocess levels are supported)
- Process operations
- Process steps (optional)

All processes involved in a production activity are contained in what is known as an as-planned bill of process (BOP); its contents are whatever concurs to manufacturing the product to which the processes refer. In detail, all processes and their sub-elements, all the tools and machines to be used, as well as the materials to be consumed in the specific production activity to be executed are contained in the as-planned BOP.



Process hierarchical structure model.

It is possible to modify a process, making changes as needed; the result is a revision of the original process.

Likewise, revisions can also be made for:

- Subprocesses
- Process operations
- Process steps

All processes have a status that is tracked and managed. For example, they can be active, obsolete, etc.

Subprocesses

In the case of complex production activities, it may be necessary to break down a process into several subprocesses. Subprocesses are made up of process operations, which, in turn and depending on their complexity, may be formed by a series of process steps.

Process operations and steps

Process operations are the main building blocks of an abstract process: during engineering, a series of process operations are linked to form the backbone of a generic process. Each process operation can exist as the result of linking of various process steps, which are optional. Process operations can be linked to different parent processes or parent subprocesses.

The concepts described in this section apply both in the context of the CLM solution and when processes are defined directly in Opcenter Execution Discrete. In the former case, Teamcenter Manufacturing is the master of process information, and no changes are applied at Opcenter Execution Discrete level.

4.2.6 Feature management

Users can now configure the specific characteristics, with values and options, of the goods that they produce. This can be obtained through the bill-offeatures, which works as the central unit to manage all the essential characteristics and all possible variations applicable to a product.

In Opcenter EX DS, it's possible to create qualification criteria based on the features listed in the bills-of-features. When a work order is created from a master plan with this criterion, the work order will automatically contain those features that satisfy the qualification criteria.

4.2.7 Change management

Operators can request changes to a specific work order; the change can affect the BOP or the part list of a specific work order. Exceptional changes affect all processes in the system; changes performed using Opcenter Execution Discrete change management affect only selected work orders.

Possible changes include:

- Add data collection to an operation
- · Add operation to a work order
- Repeat a work order operation
- · Add part/material to the part list
- Remove part from the part list
- Replace part/material in the part list
- Change part/material quantity in the part list
- Change routing (sequence of operations)
- Delete dependency between operations

Changes can be applied both to scheduled work orders and to in-progress work orders: the changes are totally managed by Opcenter Execution Discrete, so there is no constraint in applying changes at any time (after approval by a production supervisor or quality manager).

e	Operator Landing	🕈 📬 📬 📬 🕼 🧬 🖉 📑 SIEMENS
	♡ 🗐 Mode ↑↓ Şort By 🚾 WO_WO_000 × ₽ Search by Machine / SN / Contai ₽ 幸	Change Request 🛞 🗶
	Sorrer the Bolts Quarking (CUI) WCN HOVE (SKD) That Material Wingstein Profession	Notes
88 88 오	Selected Inerse 1	ADD PART Name JOD PART Group: PART AND TOOL Neal JOD PART
	Zoon 0 5 30 and Andred D 25 Sona 6. Andred D 25 Sona 8. Andred D 25 Sona 8.	ADD WORK INSTRUCTION TO SN Group: WORK INSTRUCTION TO SN Bee ADD WORK INSTRUCTION TO SN
		ADD TOOL Name ADD TOOL Selected Rems: 0
@ 	E v v v v v v v v v v v v v v v v v v v	Cancel

Requesting a change.

Splitting a released order

When required, a manager can split an already released work order into several suborders. To do this, Opcenter Execution Discrete provides a split functionality; this functionality can split a work order according to the following criteria:

- By size, to split an order into n orders of the specified size
- By number, to split an order into the specified number of orders
- By copy, to split the order into two orders: one of a specified size, and the remaining size assigned to the original order

e	Work Orders						5 🗟	도 ⁰	MENS
	💎 🗐 Mode 🛝 Şort By @E Grou	p By Search by I	dentifier	<u>بة</u>	φ			Split Work Order ${\mathfrak X} imes$, ()
	Identifier - Name	Productio	Product N	Initial Qua	Current Q	Status	Due Date Created On	Work Order	Create
	WOTESTOON C WOTESTOON	Serialized	Winglet	1	1	Complete	Feb 22, 2023 6:09	WD_WG_519	G
	WingletProcess 🖸 🖓 WingletProcess	Serialized	Winglet	10	10	New	Apr 3, 2023 3:11:5	Тури	0
뻝	W0_WG_518 C WingletProcess	Serialized	Winglet	1	1	Complete	Apr 1, 2023 11:02 Mar 30, 2023 11:0	, Sta	-
	W0_W6_517 C WingletProcess	Serialized	Winglet	1	1	Complete	Apr 1, 2023 11:01 Mar 30, 2023 11:0	Quantity	60
	W0_WG_516 C WingletProcess	Serialized	Winglet	1	0	Scrap	Apr 1, 2023 11:01 Mar 30, 2023 11:0		88
瞈	W0_WG_515 C WingletProcess	Serialized	Winglet	1	1	Complete	Apr 1, 2023 10:59: Mar 30, 2023 10:5	spir quartey	
848	W0_W6_514 C WingletProcess	Serialized	Winglet	1	1	Complete	Mar 27, 2023 3:10 Mar 25, 2023 2:10	New Work Order *	8
	W0_WG_513 [C* WingletProcess	Serialized	Winglet	1	1	Complete	Mar 27, 2023 3:10 Mar 25, 2023 2:10	WD_WG_519.1 Generate	p
	W0_WG_512 [C]* WingletProcess	Serialized	Winglet	1	0	Scrap	Mar 27, 2023 3:09 Mar 25, 2023 2:09	Quantity *	0
	Wo_WG_511 C WingletProcess	Serialized	Winglet	1	1	Complete	Mar 27, 2023 3:08: Mar 25, 2023 2:08:	5	\otimes
	Wo_WG_510 C WingletProcess	Serialized	Winglet	1	1	Complete	Mar 27, 2023 3:07: Mar 25, 2023 2:07:	New Work Order*	m
	Wo_WG_509 [C] WingletProcess	Serialized	Winglet	1	1	Complete	Mar 27, 2023 3:06 Mar 25, 2023 2:06	W0_WG_519.2 Generate	
	Wo_WG_508 [C] WingletProcess	Serialized	Winglet	1	0	Scrap	Mar 27, 2023 3:05 Mar 25, 2023 2:05	Quantity*	23
	Wo_WG_507 [7 WingletProcess	Serialized	Winglet	1	1	Complete	Mar 27, 2023 3:03 Mar 25, 2023 2:03	5	35
	Wo_WG_506 [[7 WingletProcess	Serialized	Winglet	1	1	Complete	Mar 27, 2023 3:02 Mar 25, 2023 2:02		10
	W0_W0_Sto []? WingletProcess	Serialized	Winglet	1	1	Complete	Mar 27, 2023 3:01: Mar 25, 2023 2:01:		Š
	W0_W0_S04 []? WingletProcess	Serialized	Winglet	1	0	Scrap	Mar 27, 2023 3:00 Mar 25, 2023 2:00		5
	W0_W0_S08 [[] WingletProcess	Serialized	Winglet	1	1	Complete	Mar 27, 2023 2:59 Mar 25, 2023 1:59		2
۲	W0_W0_St2 [[] WingletProcess	Serialized	Winglet	1	1	Complete	Mar 27, 2023 258L. Mar 25, 2023 1:58L.		щ
	WingletProcess	senarged	wingret	1	1	Lomplete	Mar 21, 2023 237 Mar 25, 2023 1:57		
	Selected Nerve 1								
٥	Jereves Merry 1							Cancel Split	

Splitting a work order.

4.2.8 Material consumption

Opcenter Execution Discrete displays the list of material components assigned to each operation, regardless of whether the process was defined in Opcenter Execution Discrete or transferred from the PLM system. Basically, material components are displayed as instruction information about what is to be consumed. The system allows operators to collect material usage information. Reasons to request operators to declare material usage include:

- Material usage as checklist
- · Material usage declaration as error-proofing
- Accurate as-built data collection

Opcenter Execution Discrete can manage several material types. The most relevant for production are:

- Serialized operators are required to insert the serial numbers (S/Ns) of the part to uniquely identify it. The S/N can be inserted using a keyboard or barcode scanner, or selected from a list of available numbers. S/N information is available at any time in genealogy and in as-built reporting.
- Not serialized operators are required only to insert the used quantity; this kind applies especially when there is no need to track the used part identifier (bolts, for example).

 Batch managed – operators are required to insert the identifier of the batch that the used parts are taken from. The identifier can be inserted using a keyboard or a barcode scanner, or selected from a list of available identifiers. Batch ID information is available at any time in genealogy and in as-built reporting.

Every time an operator consumes a material inserting a S/N or batch ID, Opcenter Execution Discrete checks whether the specific part is available, whether the S/N is unique, and whether it is not already used or reserved for another work order. It is also possible to define barcode rules for each material: at runtime the system will validate the scanned barcodes with the pre-defined rules preventing the Operator of assemblying the wrong material.

	Operator Task List				r 📽 📽	👷 💅 🧬 🕬 SIEMENS
尙	Est. Start: Final Material: BottlingMachine	Est. Duration: 00:45:00 SN: SN_BM_20200930_033	Remaining Time: 44:28 Workcenter: BottlingMachineAssyStation20	Status: (Active Users: SIEMENSDC\ad	Work Ord Work Ord	ler Operation: 20-Core System Assembly
29 20 20 20	Work Instruction Task for Work Instruction	MachineSottingMa Serial SN_BM_20200930_033	chine Auto-Consume Batch Materials	et on 🖉	Document viewer	
	Updated: Sep 30, 2020 3:07:44 AM	Material: Conveyor Type: Normal Part Batch ID	Quantity		2	
	Material Consumption Task for material consumption Updated: Sep 30, 2020 3:07:42 AM	Assembled Quantity: 0 Total: 1	1 UoM: u			
	E	Material: ProtectionShield Type: Normal Part Batch ID Assembled Quantity: 0 Total: 1	Quantity 1 UoM: u			
		Material: VerticalUpDown Type: Normal Part Batch ID	Quantity		-	
		Assembled Quantity: 0 Total: 2	2 UoM: u		Per S PTODUCT	
@ 8	START PAUSE SOP	COMPLETE	الله من المحمد المحم	TEAM DOCUMENT PRINT L	ABEL CHANGE SN FREEZE TARGET QUANTITY	CONTAINER CONTAINER

Collecting material consumption data.

It is also possible to define ,Co-product' materials, secondary goods that are generated during the manufacturing process.

4.2.9 Material pre-kitting

Material pre-kitting is a functionality provided by Opcenter Execution Discrete to assign parts to be used during production to each operation. Production supervisors can pre-assign S/Ns or batch IDs to an operation; in such cases, during production the operator is not required to enter the used part, but must confirm the use of the one already assigned. For high regulated environment it is also possible to configure the system in order to ask the operator to insert again the SN and let the system to validate if this corresponds with the pre-kitted one.

4.2.10 Tool usage

The usage of tools is often required during operation execution; sometimes knowing exactly which tool has been used is irrelevant, but in other instances, it is mandatory information. Opcenter Execution Discrete displays the required tool type in the operation details: Operators can view the list of required tools and may be required to enter the ID of the tool used. To enter the tool ID, operators can use the keyboard or a barcode scanner or select it from a list of available tool IDs.

4.2.11 Interlocking checks

The start and completion of an operation (or step) can be governed by the outcome of the interlocking checks enabled for it.

Interlocking checks verify whether one or more conditions have been satisfied in full in relation to the operation or step in question: If the outcome of all these checks is successful, the execution of the operation or step will either be started (inbound interlocking checks satisfied) or completed (outbound interlocking checks satisfied).

If more interlocking checks have been defined, they are executed in parallel. The system provides some out-of-the-box (OOTB) interlocking checks, but it is also possible to create custom ones.

4.2.12 Nonconformance declaration

Opcenter Execution Discrete provides runtime qualityrelated functions that allow tracking of nonconformances and defects and management of their lifecycles through a complete approval process.

Nonconformances are used to determine whether the production in progress needs to be adjusted to achieve better performance levels and better end results. The production coordinator has the task of evaluating (or sentencing) a nonconformance to decide what to do to rectify the situation. There are two types of nonconformance:

- Quality nonconformance declared when failures are found in the product that is being manufactured or in the entities involved in the production (machines, material items or tools). These entity types have an associated lifecycle (that is, a set of rules used to specify what happens and which states the entities assume when a nonconformance is declared on them)
- Change nonconformance (also called Change Request) – declared when something needs to be changed in the production workflow

e	Operator Landing	, Semens 🖓 🖓 🖓 🖓 🖉 👘 👘 Siemens
ង	🖓 🗐 Mode 🛝 Şort By 🔟 WO_WO_000 X D Search by Machine / SN / Contail. D 🛱	Browse Failures $\mathfrak{X} imes$
8 E	Covering 0:10 Coverin	Here $\nabla \Leftrightarrow \psi$ for by [Search by Identifier $\hat{\rho}$] \Leftrightarrow
20 20 20	rau tokana molyet Preferenze a 🛦	A FAIL-GOOTOT C A LeskDetection Descriptore Descriptore Lask Detection
1985 121	Selected Thems 1	MissingLaber Missing Laber Decorption Missing Laber Decorption Missing Laber
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0 191/lind h. Aterind >> 20-Scree th. Aterind >> 0 10-Services	Longsood/Winglet Undigood/Winglet Description Undigood/Winglet
æ		Selected Items 1 Page Sav 23 *
۲		
8	STARE STARE SED COMPLETE MAS	Cancel Add Falleres

Browsing the failure catalog.

Nonconformances include information about:

- Operation
- Material/tool
- Operator who declared the nonconformance
- Declaration time
- Failure reason

e	Operator Landing					ମ୍ମ କଟି କଟି କରି କରି ବି ୩ ଲି ୧୩	MENS
ධ	$\bigtriangledown \; \blacksquare_{\star}^{\; Mode} \; \Uparrow \; \underset{\star}{\overset{Sort By}{\star}} \;$	W0_W0_090	X D Search by Machine / SN / Contai	- P 🗄		Declare Non-Conformance	
8 6 11 12 13 13 13 13 14 14 14 14 14 14 14 14 14 14 14 14 14	Screw the Bolts 20 Own Hy, O'1/0 Wor, Wy, WS, 200 Frail Material: Winglet Preferred.					Saitud Walk Order Question Marchell Carlotter Nac, 1862207895 Nach Deep sealth with featuring	-
11 G A A	Selected Items 1					Weak Order * WO_WE5,509 WO_WE5,509 Some the kehz[2]	
	O 10-Lift and P	erEnd > 20-Screw th	AfterEnd			Senter ⁴ 1407 Manual Sacking Links ⁴	×
@ 					= •	Summer Loop Summer Lo	_
۵	SHOW START IN DETAILS	U A O			More	Cancel	ave

Declaring a nonconformance.

- Severity
- Description
- Status
- Quantity
- Work center

4.2.13 Nonconformance management

To close a nonconformance, a quality manager can make decisions according to a specific lifecycle: this lifecycle can be configured according to customer needs. By default, Opcenter Execution Discrete already provides a lifecycle with the following actions:

- Return to work defect is tracked in MOM and the operator can return to working on the work order
- Scrap the defect cannot be solved and the part must be scrapped
- Rework applying a rework operation will solve the problem (see rework process section for more information)
- Change apply a change to the work order BOP or bill-of-materials (BOM) to solve the issue Nonconformances include information about:
- Concession leave the nonconformance pending, awaiting decision
- Hold work center prevent executing any operation in the specified working area
- Send to engineering in the case of integration with Teamcenter Manufacturing, this choice will feed back the details to engineering, with the link to the relevant genealogy

4.2.14 Inspection master plans and inspection orders

Opcenter Execution Discrete can let you perform inspection not only during the execution of a work order, but any time it's needed. Customers can use Opcenter EX DS to generate inspection orders in addition to standard work orders. Inspection orders are based on the manufacturing context, specifically the produced material or the piece of equipment producing it. You can use the triggered quality inspections to manage any of the supported quality characteristics (attributive, variable and visual) as well as any sampling frequency (100 percent timebased or part-based). With the system properly configured, quality's nonconformances are automatically raised in the case of failures traced during the inspection.

4.2.15 Rework process

One of the possible options to fix a failure is to apply a rework process. When a quality manager decides to apply a rework on a specific defect, the system displays a list of possible rework processes according to the defect that was declared. The list of rework processes must be configured in advance in Opcenter Execution Discrete; rework processes can be created manually at the MOM level or downloaded from the PLM system.

Opcenter EX DS can associate specific rework processes with each defect configured in the system. Once the quality manager selects the correct rework process, the system creates a rework order based on that process and the operator can view the rework operations to be executed to fix the problem.

A rework order is identical to a work order from the point of view of Opcenter Execution Discrete in that it includes the following information:

- Working area
- Electronic work instructions
- Date/time information
- Materials

e	Operator Landing 📓 🖓 🖓 🧔 siemens
ង	♡ 🗐 yook ↑↓ Sen ty DEHKO_DE_Cylindu/04/57 × D Sauch by Machine / SK/ Contail. D 车
2 9 83 83 83 84 84 84 84 84 84 84 84 84 84 84 84 84	Querting: 10 Country: 10 WO: DPC/VEX_ENANDERS7 Profiles Profiles
	Selected Rene: 1 Zear: Image: Selected Rene: 1 Image: 1
? 〕 ₽	
å	มชี้สะ อเมือง มีมีสา กันว่า รีมี ของกันการ อเมือง มีมีสา กันว่า เมือง ของกันจะ เมือง ของกันจะ เมือง ของกันจะ เมือง ของกันจะ เมือง ของกันจะ เมือง ของกันจะ

Future hold set on a work order operation.

- Tools
- Part number
- Serial number
- All information about a rework order is visible both in the genealogy report and in the as-built report.

4.2.16 Preventing operation work booking

There can be situations when it is necessary to prevent working on specific work orders or work centers (quality audits, equipment maintenance and equipment problems, for example). To accommodate these situations, Opcenter EX DS provides the ability to set work orders and work centers on hold; this means that it will not be possible to work on the held-up item until a production coordinator removes the hold. Setting status to hold is an action that can be performed both by operators and by production coordinators.

4.2.17 Order WIP monitoring

Production coordinators and operators need an accurate view of what is actually taking place on the shop floor, so that they can make the right decisions to streamline production. Examples include:

- Which work orders are currently being processed
- Which plant is involved
- How much of a work order has been completed
- The outcome regarding the production of a certain product (that is, the quantities of what has been produced and what has been scrapped)

To satisfy your customers with the best possible product in the briefest time, it is essential that you have maximum visibility regarding work in progress. Opcenter Execution Discrete offers a dedicated WIP screen for viewing how the work orders are progressing in their execution. The screen displays all work orders, with an indication of the final product being produced and the current percentage of completion, as well as the plant of execution.

By selecting a specific work order, you can view information related to its operations (status, as well as produced and scrapped quantities).

4.2.18 As built

The standard as-built report page of Opcenter Execution Discrete contains information related to a specific work order. Work order data is displayed in a flat way; as-built does not contain information related to suborders.

The following information is displayed:

- List of operations, with status, estimated/actual start and end date, quantity
- List of steps

e	As Built WO_63	7533014205888903				(* 5° 5) 📬 🧔	SIEMENS
ධ 	WO_637533014	1205888903 cies Operations Steps Activity	History Print Job File	Material	Tools Work Inst	tructions Hold Rework	More		
لی ج	Identifier Description	WO_637533014205888903			Name Status	BPHD-Battery_Pack_Assembly New			
H	Production Type Estimated Start Time Actual Start Time Created On	Serialized 04/06/2021 12:23 PM			Due Date Estimated End Time Actual End Time Estimated Duration				
	Initial Quantity Reworked Quantity Plant Process	1 0 1000_A			Produced Quantity Scrapped Quantity Final Material	0 0 50105248			
	ERP Order Parent Work Order	ERP_Order_123671			Parent Batch Child Work Order	ERP_Order_123671			
©									

As-built report retrieved starting from a work order.

- List of materials that have been assembled with their quantities and/or serial numbers
- List of Co-products materials with their quantities and/or serial numbers
- List of notes that have been opened and closed by operators
- Personnel log related to an operation
- Data collection values
- List of tools
- List of transferred CNC part programs or AM print job files
- List of associated rework orders
- List of changes

4.2.19 Genealogy

Opcenter Execution Discrete tracks information related to material consumption/assembly/disassembly. The genealogy report screen displays data related to a batch, serial number or work order in a tree view.

For each identified material that is produced the system displays:

- Operations performed to produce the material
- Consumed materials
- . Quantity
- . Material definition
- . Batch ID or serial number
- Used workcenter
- Acquired data collection
- Tools used
- . Tool definition
- . Quantity
- Nonconformances
- Operators involved
- . Role
- . Start/end activity time

If a work order consumes materials produced by other orders (subassembly), all the order information is shown in the main work order genealogy tree.

Opcenter Execution Discrete provides both forward and backward genealogy: a production coordinator or operator enters the desired serial number or batch ID, and the genealogy report shows how it has been produced and/or where it has been consumed.



Genealogy report retrieved starting from a work order.

4.2.20 Work-order specific, part-based quality inspections

Opcenter EX DS permits to set part-based quality inspections as specified by the work order in the Bill of Process (BOP). The inspection counter takes into consideration the pieces produced by a specific work order. Users in the operator landing page, can be notified about the approach of a quality inspection trough a dedicated indicator displayed by the system inside the work order operation tile.

This indicator is displayed once the value set for the dedicated configuration key is reached.

You can set:

• The percentage of items to be produced that is missing to reach the configured inspection frequency for part-based inspections

4.2.21 Time-based quality inspections

Quality inspections can be activated also on a time-based criterion. The system can be set to trigger the quality inspections according to specified intervals, these specified intervals can be set at specific time intervals (time-based). The system will start the time counter once pieces are started for a specific work order operation and notify the operator that a quality inspection task must be performed when the specified time has passed. At least one quality inspection must be performed to complete the work order operation.

You can set:

• The percentage of time that is missing to reach the configured inspection interval for timebased inspections

4.2.22 Workload distribution

At shift start, production coordinators or team leaders can check the work schedule assigned to the job shop area they are responsible for, rearrange it as appropriate and distribute operations among their team members based on skills and availability.

Operations Schedule													P 6	P 👷 I	ో 💕	¢° \$°	E SIE
₽≢	Production Coordinator Dashboard > C	Operations Schedule FabricationArea															
AeroAssemblyArea	Remaining time before page refr	resh 00:36														Disable co	untdown
Level Area	8 7 © \$ < P	,⊕ ,⊕ >															
Active-Open-Queue: 0-1-1	Operation	Start Time	End Time	<u> </u>					05/03/2	022 12:11 PM	05/03/2022	12:24 PM			1		
AeroAssemblySite	Heating W0: W0_FA8_348 (ReadyForScheduring)	Estimated 05/03/2022 12:12 PM	Time 05/03/2022 12:15 PM	-	1212	1213	12114	12115	1216	1217	12110	12119	16169	1021	Telec	180	
Level Site	Machining WO: WO_FAB_248 (ReadyForScheduling)	Estimated 05/03/2022 12:12 PM	Time 05/03/2022 12:16 PM														
And the second second second	Deburring W0: W0_FAB_248 (ReadyForScheduling)	Estimated 05/03/2022 12:13 PM	Time 05/03/2022 12:17 PM														
AeroAssyCel10 AeroAssyCel10	Heating W0: W0_FA8_249 (ReadyForScheduling)	Estimated 05/03/2022 12:15 PM	Time 05/03/2022 12:18 PM														
Level WorkGel Active-Open-Queue: 0-0-0	Machining W0: W0_F48_249 (ReadyForScheduling)	Estimated 05/03/2022 12:15 PM	Time 05/03/2022 12:19 PM														
AeroAssyCell20	Deburring W0: W0_FA8_249 (ReadyForScheduling)	Estimated 05/03/2022 12:16 PM	Time 05/03/2022 12:20 PM														
Levet WorkCell	Heating W0: W0_FAB_252 (ReadyForScheduling)	05/03/2022 12:17 PM	05/03/2022 12:21 PM														
Active-Open-Queue: 0-0-1	Machining WO: WO_FAB_252 (Read)/forScheduling)	05/03/2022 12:18 PM	05/03/2022 12:22 PM														
AeroAssyCell30 AeroAssyCell30	Deburring W0: W0_fA8_252 (Read)/forScheduling)	05/03/2022 12:19 PM	05/03/2022 12:23 PM														
Level WorkCell Active-Open-Queue: 0-1-0	W0: W0_FAB_250 (ReadyForScheduling)	05/03/2022 12:16 PM	05/03/2022 12:19 PM														
o∞ AeroAssyStation10	W0: W0_FAB_250 (ReadyForScheduling)	05/03/2022 12:17 PM	06/03/2022 12:21 PM														
AeroAssyStation10	W0: W0_FA8_250 (ReadyForScheduling)	05/03/2022 12:17 PM	05/03/2022 12:21 PM														
Active-Open-Queue: 0-0-0	W0:W0_FA8_251 (ReadyForScheduling)	05/03/2022 12:17 PM	05/03/2022 12:20 PM														
AeroAssyStation20 AeroAssyStation20	W0:W0_FA8_251 (ReadyForScheduling)	05/03/2022 12:17 PM	05/03/2022 12:22 PM														
Level: Unit Active-Open-Queue: 0-0-1	W0: W0_FAB_251 (ReadyForScheduling) Deburring	05/03/2022 12:18 PM	05/03/2022 12:22 PM							No Tim	e Ranges						
AeroAssyStation30 AeroAssyStation30	WOI WO_PAB_247 (Queue)																
Level Unit Artise Oran Oran # 0-1-0	Active 🚯 Complete 🚫 P	artial 🔘 Open : 🖱 Op	sen (Ready)														

This is most effective when operations modeled in the processes have minimum operator skill requirements for their execution.

Production coordination dashboard.

When such association is performed, operators logging into Opcenter EX DS will find operations directly assigned to them. Of course, it is possible to assign the same operation to any number of operators.

4.2.23 Labor tracking

Opcenter Execution Discrete enables production coordinators to monitor work booking times related to operations.

For each work order operation, Opcenter Execution Discrete displays:

- Status
- Estimated start/end time
- Actual start/end time
- Labor duration

For each work order operation, production coordinators can view time details of each operator. For each operator, Opcenter EX DS provides:

- User identity
- Activity (start, pause and complete)
- Timestamps

Production coordinators can amend collected data for completed operations both at work order operation and at operator level.

e	Work Order 20200728_002		r 19	⊠ ⁸ ⊠ [®] (£ [©] SIEF	MENS
囗	\$ \$ \$ \$	Production Coordinator Time Update 20200804_001 > Work Order 20200728_002	Edit Estimated Time		0
3	20200728_001		Actual Start Time Jul 28, 2020	7:03 AM	
<u>ب</u>	Final Material: FAR_SER001	V I waa V sont by Identifier	Actual End Time		
୍ଦ୍ଧିକ	status, complete		Jul 28. 2020	7:05 AM	
***	Final Material: FAR_SER001 Status: Complete	Status: Complete Sequence: 10	Labor Time (hours, minutes, s	0	
	20200802_001 Final Material: FAR_SER001 Status: Aborted				
0 () () ()	Einal Material: FAR_SER001 Status: Pause				
8	<	Selected Items: 1 Showing 1 to 1 of 1 entries		Cancel Save	

Activity track record on a work order.

4.2.24 Team work

Teams are groups of users that can be formed for the purpose of performing production operations together.

Although roles represent a more permanent way to group individuals according to their know-how or position within the business hierarchy, teams are flexible and designed to be created on-the-fly and disbanded when no longer necessary (for example, when two or more operators are needed to perform an assembly operation because the part is too large to be assembled by one person).

A single team member can start/pause/complete work order operations on behalf of the entire team. Every one of the group members takes responsibility for the actions of the other team members as a collective responsibility.

4.2.25 Nonproductive activities

A nonproductive activity is an activity performed in a work center that is not directly related to a production cycle and/or to a specific work order, but that still needs to be tracked and recorded.

Some nonproductive activities may be totally unrelated to production entities, while others may be related to them. Examples of nonproductive activities include, for instance, cleaning machines and tools, general maintenance, training, mentoring, assistance, meetings and administrative activities.

4.2.26 Electronic signature and buy-in

Opcenter Execution Discrete implements electronic signatures during operation work booking (see operation work booking section for more details) to represent validation and buy-in; only certified users can execute and complete an operation and sign it.

The operator or supervisor who has the appropriate authorization oversees signing off on all the operation data, regardless of the users who worked on the operation and filled in checklists or declared tools and material consumption.

For each operation, more than one person can be required to provide electronic signature. The buy-in is recorded in the as-built summary.

e	Operator Landing	ୱେ ^ଅ ନ୍ସ [®] ୟୁ [®] ହେ [®] ନ୍ଥ [®] ହ	NS
尙	♡ 🗐 Mode 🏠 Şort By DEWO_DE_Cylinder04057 X D Search by Machine / SN / Contai D 批	Electronic Signature	×
₩ 4	Culture Control Contro	Password *	
0	Solected Item: 1 Zoom: 0 10-Cyl PrintAtterfind 0 20-Cyl PrintAtterfind 0 30-Cyl PostAtterfind 0 40-Cyl Visua		
@ 	START PAUSE SUP COMPLETE E CAR	Cancel Validate U	ser

Electronic signature required upon material consumption.

4.2.27 Certifications

A certification represents an authorization that is created ad hoc with particular characteristics and then assigned to a user or role and defines the sphere of action within which he/she can operate. Users and roles can be certified to:

- Perform a certain task (that is, start, pause or complete a specific operation)
- View the details of a specified operation
- Operate in a specific location (workcenter)
- Use a specified machine
- Use and/or produce a specified material

The definition of a certification may include:

- One or more material definitions
- One or more machine definitions
- One or more locations (workcenters)
- · One or more skills, optionally with their levels
- Any combination of the above Opcenter Execution Discrete adopts access control through certifications to simplify the task of tracking

where within a production plant who can perform what to produce which materials using which machinery owning which skills.

Possessing a certification that is currently valid is essential for a user/role to perform runtime operations; whenever a certification is assigned to a user or role, an expiration date is required. The validity of a certificate is not indefinite.



Creating skills.

4.2.28 Result management

Shop-floor operators can declare a result upon operation completion of each serial number or batch, so that the execution of the failed activities can be reiterated (either immediately or at a later time) until their outcome is positive (that is, "as expected"). This is the default strategy followed by the system when result declaration is adopted.

In addition to the native result types provided in Opcenter EX DS to declare positive and negative results, it is possible to configure custom result types that may better satisfy specific needs. After a result has been declared, if necessary, authorized users who possess the appropriate user rights can override its value by performing an amend operation.

It is also possible to amend a result's strategy. For example, let's say that the corrective action initially associated to a result becomes unnecessary or is no longer valid. In this case, depending on the situation, the user can choose to amend the result's strategy by either:

- · Removing it: in this case, no corrective measure will be adopted
- Switching to a different corrective action

4.2.29 Work order operation execution using the high automation user interface Opcenter Execution Discrete uses the high automation user interface to monitor and control the production and delivery of products and services. The high automation user interface allows the user to select a machine instance so the high automation details user interface will show the details of the work order operation active on the selected machine. Once the machine is selected, the information is saved in the database and re-used after the next login of that user.

The high automation user interface uses the signals about the operations performed on the machine, such as start, complete and assemble and displays the correct corresponding data in real time. The user can perform standard functions such as adding a note or a defect, among others.

The high automation user interface contains all the documents and material to be consumed that are associated with the active work order operation on the selected machine.

While configuring the system, the default layout of the high automation landing page can be changed to enable the display of run-time tasks, similarly to what is done in the standard operator landing page.

4.2.30 Production execution in offline mode

Opcenter EX DS comes provided with the capability to execute production in offline mode (that environments without connectivity to the Opcenter EX DS server.).

In such cases, if a dedicated app is installed on mobile devices, shop floor operators can manage operations directly from their mobile devices.

Once selected for offline execution, and their content is downloaded on the mobile device, operations remain visible in the operator landing page. However no actions are permitted: operations remain locked until they are checked in again.

The following actions can be performed while working offline:

- Starting work order operations and steps
- Pausing work order operations
- · Completing work order operations and steps
- Consuming materials
- Using tools
- Displaying documents
- Collecting data
- Uploading documents
- Creating quality non-conformances

As an operator, you can:

- Perform the check-out of work order operations on the mobile device and thus implicitly start offline sessions
- See the content of the related offline session (in terms of involved work order operations) from the offline Sessions page
- Upload production execution data from the mobile device to Opcenter Execution Discrete once the work order operations are completed, or in case you want to proceed with execution in online mode
- Amend the content of uploaded offline actions, in case of failures
- Perform the check-in of offline actions and offline sessions to conclude production execution in offline mode

4.2.31 Electronic work instructions

The EWI is a technical package of information defined within the authoring environment and consists of all associated data required within the MOM system to perform the necessary manufacturing, assembly or test activities.

In a paper-based environment, operators can spend hours looking for the correct WI to be used for a specific operation; moreover, the document can be damaged or illegible. Opcenter Execution Discrete provides the operator with only the EWI related to the specific task at hand. However, the document is always in an electronic format that guarantees the usability of the instructions.

It is possible to specify EWIs at different levels in the manufacturing process, which is typically defined hierarchically with two nested levels: operations and steps.

The following types of data are included as part of the EWI and are displayed within the MOM system at the appropriate point of operation:

Operation or step text – instructional text can be authored to guide operators at runtime to perform the right operations in the right sequence. It is also possible to define special notes, warnings and cautions

- Parts to be used at operation/step level a list of items required at each operation/step with appropriate attributes (part number, description, quantity, classification, type, location, etc.). Part images such as 2D drawings can also be attached
- Resource (tooling) to be used at operation/step level – a list of tools required at each operation/ step with appropriate attributes (tool type, description, quantity, classification, location, etc.).
 Tool images such as 2D drawings can also be attached
- Images (2D drawings, photos, etc.) various media types can be attached at operation/activity level and can be displayed with the appropriate viewer in the MOM system
- Documents (Word documents; Excel sheets, PowerPoint slides and PDF reports/specifications)

 various datasets can be attached at operation/ step level and can be displayed with the appropriate viewer in the MOM system

The association between an operation and the EWIs to be displayed can be performed manually in the dedicated Opcenter Execution Discrete screen or by downloading the information directly from the PLM system. Display files in PLMX Viewer in 3D Using Opcenter Execution Discrete helps you display PLMX files in 3D to perform your job with greater ease and precision. Operators can have a visual insight on how to perform a certain task thanks to the 3D file visualization. For example, you can display a certain object in 3D to see in detail the exact point where a hole should be drilled or where a rivet should be inserted. However, operators will need to perform additional implementations to fully exploit the functionality.

4.2.32 Data collection

During production, it is often required to collect various manufacturing data manually (for example dimensions, process parameters, etc.). This information can differ for each work order and work order operation. Opcenter Execution Discrete offers the ability to collect data during the execution of specific operations. Operators on the shop floor execute the required activity and fill in dedicated forms with the required data. All of the entered data is visible in the as-built report screen and genealogy report screen.



The 3D viewer in the operator's terminal.

Data collection values can be also acquired directly from the automation layer at runtime. You can achieve this by either integrating the Opcenter Execution Foundation Automation Gateway linking machines/data collections to automation node instance parameters, or by leveraging Opcenter Connect MOM to read datagrams. A data collection form may be associated with a work order operation or step in its entirety, or to individual serial numbers.

To enable manufacturing data collection, Opcenter EX DS provides an engineering environment for creating forms with fields for specified information; these forms can be linked to operations manually and displayed for operators during production activities; operators are always asked to collect the right set of information for each operation.

When creating forms, it is possible to define:

- · Sets of data to be collected
- Type of data to be collected (number, text, etc.)
- Range and limits (if the collected value is out of range, Opcenter EX DS will notify the operator)
- Mandatory values (if mandatory values are not collected, it is not possible to complete the operation and proceed with the next one)

4.2.33 Managing screwing operations

Using Opcenter Execution Discrete can help you manage screwing operations. Where the integration is correctly configured Opcenter EX DS will send values to the automation layer and receive the corresponding result, so you can accurately trace the related data during production execution. You can also use screwing tools when executing work orders. A dedicated task on the operator landing page enables you to activate the screwing tools to monitor the result of the operation. In addition, it is possible to see the values collected on the genealogy page and on the workorder history.

4.2.34 Additive manufacturing

Additive manufacturing is an industrial process used to create a three-dimensional object in which successive layers of material (typically metal powders, plastic, concrete) are formed using computer control. Opcenter Execution Discrete supports additive manufacturing through the following functions.

 "Print job files" management – It is a file that contains information used by a 3D printer to create products by means of additive manufacturing processes. Using custom plugins, Opcenter EX DS can retrieve the file from a print job file repository, present the print job file to the shop floor operator during operation execution and download it on the correct 3D printer

Print job files can be associated with a single work order operation or with an execution group – their contents can be subsequently transferred as needed to the machine associated with the execution group. Thanks to this possibility, you can launch production as specified in the print job files for all the work order operations making up the execution group in a homogeneous manner

Track and display the genealogy of powder material batches – additive manufacturing material is available as powder material batches. Each batch represents the container that holds the powder material item. A powder material batch is thus raw material for a 3D printing operation. Opcenter Execution Discrete supports the capability of reusing powder material from multiple batches. Powder material batches can also be split and mixed to form new batches. Powder material batches assume a status and thus have lifecycles. The history of batches mixing is called powder material genealogy

• Track and display the lifecycle of substrates: a substrate is the build plate upon which 3D objects are printed by using a 3D printer. Since final items are developed upon substrates, Opcenter Execution Discrete treats substrates as specialized tools, which is why they are created as tool definitions and instantiated as tool entities. Substrates are configured and associated with work order operations. The substrate lifecycle represents the states that a substrate assumes, and transitions to, because of the operations performed on it



Powder genealogy

More information is available in the Closed-Loop Manufacturing (CLM) – Implementation Guide.

4.3 Opcenter EX DS features for intraplant logistics

4.3.1 Handling units and transport operations

When a logistic request is declared, it can be accepted to start the movement of the required item or rejected. When accepting a logistic request, it is mandatory that at least one source buffer be specified.

When a logistic request is accepted, a new transport operation to fulfill the request is automatically generated.

The various states of the transport operation specify the various phases of the transport operation 's execution.

Once the transport operation has been released and appropriately configured, the transport operation will be started. The required item(s) will be pulled from a source buffer and then placed into a handling unit.

Handling units are designed specifically to identify a set of materials that must be moved together from source to destination. Handling units can start to proceed toward the destination buffer if they are in dispatchable status. Once the handling unit is set in motion, it is in on route

status: its contents are transported to the destination buffer. At this point, the transport operation has been completed and the contents of the handling unit can be unloaded.

The transport operation history traces the details of the operation's execution, whereas the handling unit history traces the various phases of the handling unit's progression.

4.3.2 Containers and container types

Containers are entities configured to hold and move semifinished products during the production process. Containers represent physical entities where the materials can be loaded and stored for the time between one operation and the next. Containers can be re-used.

It is possible to define templates (container types) from which many different containers can be defined inheriting the same configurations and associated documents.

4.3.3 Transportation management

All activities regarding the transportation of items within the boundaries of a plant can be classified as related to transportation management, also referred to as intraplant logistics (IPL).

Here are some examples of such activities:

- Raw materials are moved from a storage area to the machine that will process them
- Semifinished products are transported from one machine to another so that they can undergo additional processing
- Final materials are moved to another storage area prior to being packaged and subsequently shipped out from the plant

- A specific raw material is transported upon request from a storage area to a specific location inside the plant to permit the continuation of production activities
- A defective piece is pulled from the normal flow of activities and moved to a specific location so that it can be checked, reworked or scrapped

4.3.4 Logistic classes

A logistic class groups similar materials or tool definitions for transportation or packaging. For example, logistic class "burner pipes" groups all burner pipes that are produced in the same plant and need to be transported.

Opcenter EX DS comes with a predefined default logistic class, but it is possible to create custom logistic classes tailored to your needs.

4.3.5 Buffer definitions and buffers Buffer definition

A buffer definition is an abstract representation of a specific area or accessory (for example, a wagon or cart) used to store items. The configuration of a buffer definition considers the maximum weight, maximum volume or maximum quantity as well as the unit of measure to be used when defining the overall capacity allowed. It is possible to configure a buffer definition to allow the storage only of specific materials and/or logistic classes, specifying minimum and maximum quantities as well as threshold and target quantities for automatic replenishment.

Buffer

A buffer is the runtime instantiation of a buffer definition; therefore, it inherits its configuration. It represents the actual area or accessory for storing specific material to be used or consumed during production within the plant.

4.3.6 Logistic requests

Declaring a logistic request is essential to transportation management within your production plant as it specifies which materials are required and where they need to go.

0 -					<u> </u>						
VE	Mode	Sort By Search t	by Identifier	2 *	ζ						
Identifi	er	Name 👝	Description	Status	Workcenter	Max. Value	Buffer Defi	Buffer Defi	Buffer Defi	Capacity Type	Buffer Defini
Bottling	Machi [BottlingMachineLin	BottlingMachineLin	Released	IndMachineryAsse	100	BottlingMachineLine	BottlingMachineLine	A	Quantity	BottlingMachineLine
& Bottling	Machi	BottlingMachineSto	BottlingMachineSto	Released	IndMachineryAsse	10,000	BottlingMachineSto	BottlingMachineSto	Α	Quantity	BottlingMachineStor
Bottling	Machi [BottlingMachineSto	BottlingMachineSto	Released	IndMachineryAsse	10,000	BottlingMachineSto	BottlingMachineSto	A	Quantity	BottlingMachineStor
📥 Bottling	Machi	BottlingMachineSto	BottlingMachineSto	Released	IndMachineryAsse	10,000	BottlingMachineSto	BottlingMachineSto	А	Quantity	BottlingMachineStor
Tractor/	xleLin [C	TractorAxleLinePrep	TractorAxleLinePrep	Released	HeavyEquipAssemb	100	TractorAxIeLine	TractorAxleLine	A	Quantity	TractorAxleLine
L Tractor	xleSt []	TractorAxleStorageF	TractorAxleStorageF	Released	HeavyEquipAssemb	10,000	TractorAxleStorage	TractorAxleStorage	A	Quantity	TractorAxleStorage
L Tractor	xleSt []	TractorAxleStorageF	TractorAxleStorageF	Released	HeavyEquipAssemb	10,000	TractorAxleStorage	TractorAxleStorage	А	Quantity	TractorAxleStorage
L Tractor	xleSt []	TractorAxleStorageF	TractorAxleStorageF	Released	HeavyEquipAssemb	10,000	TractorAxleStorage	TractorAxleStorage	A	Quantity	TractorAxleStorage
📥 Assemb	lyLine [C	WingletLinePrepara	WingletLinePrepara	Released	AeroAssemblyArea	100	AssemblyLine	WingletLine	A	Quantity	WingletLine for Asse
📥 Assemb	lyStor [C	WingletStorageFro	WingletStorageFro	Released	AeroAssemblyArea	10,000	AssemblyStorage	WingletStorage	А	Quantity	WingletStorage
👃 Assemb	lyStor [C	WingletStorageFro	WingletStorageFro	Released	AeroAssemblyArea	10,000	AssemblyStorage	WingletStorage	A	Quantity	WingletStorage
👃 Assemb	lyStor [C	WingletStorageFro	WingletStorageFro	Released	AeroAssemblyArea	10,000	AssemblyStorage	WingletStorage	A	Quantity	WingletStorage
Selected It	ems: 0										

Buffers listing

Automatic logistic request generation is the most common scenario. By importing a dedicated signal rule installed with Opcenter Execution Discrete, logistic requests are generated automatically by the system whenever the buffer level falls below a defined threshold.

However, it is also possible to declare logistic requests manually, if desired. A manual logistic request can consist in a single material request.

4.3.7 Material request and transport operation improvement

Declaring a logistic request is easier and quicker since all system-generated parameters are automatically filled. In addition, the management of existing logistic requests has been improved, providing the subscription to notifications that are sent whenever a new one is declared, and the possibility of sorting them by priority to identify the most urgent. At run time, if the operator chooses to enable the automatic consumption of batches, the system automatically consumes the batches contained in the buffer associated with the active machine instead of creating a batch on-the-fly.

4.3.8 Kanban calls and line side

position management

Line side positions represent specific areas or accessories (for example, racks) allocated to store materials within the manufacturing environment to constitute what can be called a line side inventory. Line side positions and related kanban calls can be managed either manually or automatically if properly configured at run time. They can be configured specifying the initial quantity and the maximum capacity allowed. In case of automatically managed line side positions, it's possible assign thresholds to set target quantities and priorities for replenishment. When the threshold is reached or falls below the configured value, a Kanban call is sent to the warehouse to request a replenishment using a kanban output message.

5 Collaborations

5.1 Closed-loop manufacturing execution

Closed-loop manufacturing enables customers to seamlessly unite product engineering and process planning with production execution; this is a key differentiator of the Siemens portfolio.

Opcenter Execution Discrete works in conjunction with Teamcenter Manufacturing and Teamcenter Quality to deliver a holistic vision through superior information access across different business domains. A tight relationship between the two products supports efficient engineering changes. Any change defined at the manufacturing planning level can be considered and implemented quickly and properly at the shop floor level by means of accurate and repeatable communication.

Downstream from PLM to MOM, Opcenter EX DS supports:

- A consistent view of manufacturing technical information authored in Teamcenter Manufacturing, including the failure catalog and quality characteristics authored in Teamcenter Quality
- Real-time data views in Teamcenter Manufacturing as rationale for manufacturing engineers before releasing changes to execution

 A structured model of the manufacturing plant in Teamcenter Manufacturing, enabling manufacturing engineers to better detail the content of the bill of process

Upstream from MOM to PLM, Opcenter EX DS provides out-of-the-box capabilities to create issue reports in Teamcenter Manufacturing (Teamcenter Issue Management) and to enrich them with relevant content.

The integration between Opcenter Execution Discrete and Teamcenter Manufacturing is available only for selected product versions; please refer to specific documentation.

5.2 Opcenter Scheduling integration

As Opcenter Execution Discrete is focused on operations and the work centers where such operations are executed, the ability to schedule operations based on constraints provides a powerful tool to optimize activities and fulfill planned delivery time.

Operations inside Opcenter EX DS can be assigned to a work center.

Production planners can retrieve the set of operations and their work center inside a predefined time interval using Opcenter Scheduling, using it to create the best scheduling and push back scheduling proposals to Opcenter EX DS. Supervisor can always adapt it to specific, real-time needs.

Opcenter Execution Discrete supports two-way communication with Opcenter Scheduling:

- The Opcenter EX DS operator can access all planned operations available in the work center sorted by estimated start time. Operations will also have suggested equipment on which the operation should be started, so that the operator will have more information about when and where to start the operation.
- Production planners have access to the list of operations, and according to the constraints can schedule them to streamline equipment utilization. Planners can also be informed of any order/ operation in scheduling that has been modified at the shop floor. The integration between Opcenter Execution Discrete and Opcenter Scheduling is available only for selected product versions; please refer to specific documentation

5.3 Siemens Xcelerator Share integration

Siemens Xcelerator Share is a cloud-based collaboration service for software subscriptions, which provides secure cloud storage for synchronizing data across the Siemens Xcelerator.

Opcenter EX DS is part of Siemens Xcelerator Share to cover the following use cases:

- Intracompany collaboration: Sharing manufacturing and quality information with colleagues that don't have immediate access to Opcenter 1EX DS
- Documents captured from the shop floor during production, for example, test results, measurement results, etc.
- Nonconformance documents, including their original and marked up attachments

This removes the constraint that the involved user must have dedicated and immediate access to Opcenter EX DS or Teamcenter MPP, or both.

2. External collaboration: Sharing product history information with installation and servicing personnel in the field (this depends on network security configuration)

5.4 Additive manufacturing network integration

Opcenter EX DS can be integrated with the Siemens Additive Manufacturing Network, which is a Siemens Digital Industries Software cloud-based solution designed to optimize execution activities in additive manufacturing contexts, from sales orders to delivery.

With this integration, a series of items defined in the Additive Manufacturing Network can be imported into Opcenter EX DS to streamline shop floor operations. Additionally, the Additive Manufacturing Network can be notified of any changes in Opcenter EX DS production status. This provides overall visibility on the production process.

6 Integration with automation, physical devices and third-party systems system

6.1 CNC integration

Opcenter EX DS is frequently used to manage production steps that involve machining via CNC devices. The way such devices are operated may vary according to several factors including material, machine, tools and operation. The CNC part program is the element that drives a CNC device to work as requested by Opcenter Execution Discrete. In this context, it is essential to have an automatic transfer of the CNC part program to CNC devices.

Part program packages defined in an external DNC system can be imported into Opcenter Execution Discrete and associated with the defined machines. At runtime, the system prompts the operator for the correct program to download to the machine; upon operator confirmation, Opcenter Execution Discrete triggers the DNC system to download the correct part program to the correct CNC machine.

The DNC system is external to Opcenter Execution Discrete and includes the capability to write a custom connector to any DNC system available at the customer's site.

6.2 Setpoints

Setpoints are used to drive how a machine or a tool must behave at runtime, thereby eliminating the need for shopfloor operators to perform manual adjustments.

On their own, setpoints are merely empty containers: in order to function, they must be filled with one or more variables.

For example, if a certain machine must reach a certain temperature before it can be used in executing a work order operation, then the setpoint to be associated to that specific machine will contain variable "temperature", the value of which is equal to that specific temperature.

During runtime, the setpoint variable's value will be transferred to the machine: the machine, which is linked to the automation layer, must necessarily reach the temperature specified in the setpoint before it can be used.

Setpoints can be associated to the following items thus declaring their compatibility:

- Equipment types and equipment configurations
- Tool definitions and tools.

If you associate a setpoint to an equipment type or tool definition, the same setpoint will be inherited by all machines or tools generated from the equipment type or tool definition to which the setpoint was associated.

6.3 Structured-message exchange

Certain activities can be automated during production execution by adopting a "structured-message exchange" approach.

With appropriate scenario configuration in Opcenter Execution Discrete, this approach can be adopted to exchange messages between the MES layer and the shop floor to automatically:

- Start and complete operations
- Create and resolve nonconformances by machines or work centers
- Consume material during the execution of operations
- Collect data and quality characteristics during the execution of operations
- Use tools during the execution of operations

Opcenter EX DS can exchange messages through interaction with the Opcenter Connect MOM product.

6.4 Barcode management

Opcenter Execution Discrete provides the possibility of configuring barcode rules to validate a barcode string.

Once created, barcode rules are empty containers which can be associated with rule parts in any combination you deem necessary, each of them containing a regular expression which will be used to validate the barcode string.

Whenever a barcode string is received from a barcode reader, the system automatically retrieves the corresponding rule from the associated material. If the rule is not found, the system retrieves it from the functional code or, as a last option, from the default barcode rule that is provided out-of-the-box and can be set thanks to a dedicated configuration key.

As a product engineer or production coordinator, you can:

- Enable the dedicated configuration key for setting a default barcode rule
- Create a barcode rule
- Configure the rule parts
- Associate a material to the barcode rule
- Associate a functional code to the barcode rule

As an operator, you can scan the barcode to validate the material to be consumed. If it matches the barcode rule, the material can be consumed.

6.5 Semiautomatic acquisition of values

If the system is properly configured and linked to the shop floor via the Opcenter Execution Foundation Automation Gateway App, it is possible to acquire values from the field.

The operator can acquire the values related to data collections, tools/substrates and material tracking units without the need to insert them manually.

The semiautomatic acquisition is possible due to the mapping of parameters with the variables coming from the field, via the Opcenter Execution Foundation Automation Gateway App.

For data collections, the field values acquired are related to work instruction parameters.

For materials, the operator can acquire the serial number, batch ID or quantity to be consumed during an assembly operation, or he/she can enter them manually.

For tools/substrates, the operator can acquire the ID of the tool/substrate to be used, the usage counter and the time duration, or enter them manually.

Information related to the acquisition from the field is traced in both the as-built and genealogy pages.

6.6 Label printing

Opcenter Execution Discrete offers the possibility of printing labels containing barcodes, text or images for:

- Work orders
- Work order operations
- Material tracking units

7 Conclusion

Siemens Digital Industries Software is driving transformation to enable a digital enterprise where engineering, manufacturing and electronics design meet tomorrow. Siemens Xcelerator helps companies of all sizes create and leverage a comprehensive digital twin that provides organizations with new insights, opportunities and levels of automation to drive innovation.

As part of Siemens Xcelerator, Opcenter Execution Discrete is used to implement a tailored MES for complex job-shop organized factories.

Thanks to the long list of out-of-the-box features provided as well as the innovative technology that delivers scalability and multi-plant architecture, Opcenter EX DS is well suited to help manufacturers of complex products to realize Industry 4.0.

Siemens Digital Industries Software

Americas: 1 800 498 5351 EMEA: 00 800 70002222 Asia-Pacific: 001 800 03061910 For additional numbers, click <u>here</u>. Siemens Digital Industries Software helps organizations of all sizes digitally transform using software, hardware and services from the Siemens Xcelerator business platform. Siemens' software and the comprehensive digital twin enable companies to optimize their design, engineering and manufacturing processes to turn today's ideas into the sustainable products of the future. From chips to entire systems, from product to process, across all industries, Siemens Digital Industries Software is where today meets tomorrow.

siemens.com/software

 \circledast 2023 Siemens. A list of relevant Siemens trademarks can be found <u>here</u>. Other trademarks belong to their respective owners.

63133-D20 5/23 K